



GOODYEAR® RH-4A+

GOODYEAR'S BEST E-4+ HAULAGE TIRE FOR CUT PROTECTION AND WEAR IN HARD ROCK UNDERFOOT CONDITIONS

■ MADE TO WORK OVERTIME

Extra-deep E-4+ tread depth with high net-to-gross pattern and optimized footprint pressure promotes long hours to removal

■ KEEPS ITS COOL

Centerline blading, shoulder lug pockets and shoulder lug side notches help cool the tire to enhance casing durability and maximize TKPH

■ DEFENSIVE SPECIALIST

Durawall Technology™* improves lateral stiffness, cut protection and casing durability



■ BROAD SHOULDERED

Wide-molded rim width^Δ promotes enhanced casing durability

■ FIRMLY PLANTED

Wider bead^Δ promotes enhanced lateral stability



GOODYEAR
OFF-THE-ROAD



GOODYEAR® RH-4A+



UNDERFOOT CONDITIONS

ROCK



AGGREGATES



ENGINEERING DATA

DIMENSION	RIM WIDTH/ FLANGE HEIGHT (in)	TREAD DEPTH (mm / 32nds in)	INFLATED DIMENSIONS ¹		LOADED TIRE ¹	
			OVERALL WIDTH (mm / in)	OVERALL DIAMETER (mm / in)	LOAD SECTION & GROWTH (mm / in)	STATIC LOADED RADIUS (mm / in)
27.00R49	19.5 / 4	83.0 / 105	758 / 29.8	2,697 / 106.2	861 / 33.9	1,237 / 48.7
33.00R51	24.0 / 5	94.0 / 118	942 / 37.1	3,063 / 120.6	1,070 / 42.1	1,365 / 53.7
40.00R57	29.0 / 6	98.0 / 124	1,173 / 46.2	3,576 / 140.8	1,306 / 51.4	1,600 / 63.0
46/90R57	29.0 / 6	98.0 / 124	1,164 / 45.8	3,571 / 140.6	1,321 / 52.0	1,600 / 63.0
59/80R63	44.0 / 5	115.6 / 145	1,496 / 58.9	4,023 / 158.4	1,730 / 68.1	1,775 / 69.9

LOADS & INFLATION for off-the-road haulage service at 50 km/h (30 mph) maximum speed

DIMENSION	STAR MARKING	LOAD SPEED INDEX	LOADS PER TIRE IN KILOS / LBS AND INFLATION BAR / KPA / PSI†											
			KILOS LBS	5.50 / 550 / 80	5.75 / 575 / 83	6.00 / 600 / 87	6.25 / 625 / 91	6.5 / 650 / 94	6.75 / 675 / 98	7.00 / 700 / 102**	7.25 / 725 / 105	7.5 / 750 / 109	7.75 / 775 / 112	8.00 / 800 / 116***
27.00R49	**	223B	KILOS	22,400	23,000	23,600	25,000	25,750	26,500	27,250				
			LBS	49,400	50,700	52,000	55,100	56,800	58,400	60,000				
33.00R51	***	238B	KILOS	32,500	33,500	34,500	35,500	36,500	37,500	38,750**	40,000	40,000	41,250	42,500***
			LBS	71,500	74,000	76,000	78,500	80,500	82,500	85,500**	88,000	88,000	91,000	93,500***
40.00R57	**	250B	KILOS	50,000	51,500	53,000	54,500	56,000	58,000	60,000				
			LBS	110,000	113,500	117,000	120,000	123,500	128,000	132,500				
46/90R57	**	252B	KILOS	53,000	54,500	56,000	58,000	60,000	61,500	63,000				
			LBS	117,000	120,000	123,500	128,000	132,500	135,500	139,000				
59/80R63	**	268B	KILOS	82,500	85,000	90,000	92,500	95,000	97,500	100,000				
			LBS	182,000	187,500	198,500	204,000	209,500	215,000	220,500				

To learn more about the Goodyear RH-4A+, contact your local authorized Goodyear Dealer or visit goodyearotr.com

TOTAL MOBILITY



Trusted Products
Specialized OTR innovations to help lower operating costs.



Reliable Services
Expert worldwide support to help you optimize operations.



Tire Management Solutions
Powerful management tools to help you improve productivity.

goodyearotr.com

¹Engineering data is estimated. | [†]Tire loads and inflation conform to the 2021 standards set forth by The Tire & Rim Association and The European Tyre and Rim Technical Organisation.