

DUNLOP[®] SP-T9



A RADIAL CONSTRUCTION TIRE FOR MIXED ON- AND OFF-ROAD SERVICE

The Dunlop SP-T9 is designed for road graders and small loaders to help deliver enhanced traction in soft underfoot conditions. Suitable for applications up to 25 mph, this tire features a high-tensile steel cord ply that delivers maximum strength and cut resistance for confidence on rough terrain.



DUNLOP® SP-T9

A RADIAL CONSTRUCTION TIRE FOR MIXED ON- AND OFF-ROAD SERVICE



- **Wide, non-directional tread design** offers excellent control and handling with minimal soil disturbance
- **High-tensile steel cord ply** for outstanding strength and cut resistance
- **Large center tread blocks** help to enhance comfort for a smoother ride

The Dunlop SP-T9 is available in the following sizes and load ranges:



Tire Size	Bias / Radial	Rim	Index LR	TT/TL	Ind Code	Non Skid	Weight	Rim Width & Flange	Overall Width	Overall Diameter	Static Loaded Radius	Rolling Circumference	Product Code	Material ID
							lbs	in	in	in	in			
335/80R18	Radial	18	145A2	TL	E/G/L3	23/32"	108.9	9" or 11" 1.0" flange	14.84	39.96	19.21	117.72	272030089	163236
365/70R18	Radial	18	146A2	TL	E/G/L3	23/32"	117.2	9" or 11" 1.0" flange	15.75	39.37	17.24	114.76	272030109	163240
405/70R18	Radial	18	153A2	TL	E/G/L3	25/32"	133.6	13" 1.0" flange	17.80	42.13	18.15	121.46	272030119	163242
335/80R20	Radial	20	147A2	TL	E/G/L3	23/32"	117.7	11", 12", 11" SDC, or 12" SDC 1.0" flange	14.41	42.36	18.66	123.62	272030319	163244
365/80R20	Radial	20	153A2	TL	E/G/L3	25/32"	134.9	11", 12", 11" SDC, or 12" SDC 1.0" flange	15.75	44.37	19.41	129.33	272030169	163246
405/70R20	Radial	20	155A2	TL	E/G/L3	24/32"	150.1	11", 12", 13", or 13" SDC, W14L/DW14L (14") 1.0" flange	17.80	44.13	19.17	127.56	272030219	163248

To see how the Dunlop SP-T9 can help your fleet save money, contact your local authorized Dunlop Dealer.
goodyearotr.com

