
GOODYEAR® OFF-THE-ROAD

PRESSURE RECOMMENDATIONS FOR CATERPILLAR.

GET THE MOST OUT OF YOUR GOODYEAR OTR TYRES

Maximise your Caterpillar and Goodyear OTR tyres potential by using the correct pressure.



GOODYEAR
OFF-THE-ROAD

Radial Tyres for CATERPILLAR Compact Wheel Loaders



Models	Size	Inflation Recommendation ¹				POWERLOAD	GP-3E	TL-3A+	RL-5K
		kPa		Psi		100 (L2)	100 (L3)	125 (L3+)	250 (L5)
		Front	Rear	Front	Rear				
906	405/70R18	350	225	50	32				
907	405/70R18	350	225	50	32				
908	405/70R20	375	250	54	36				
910	15.5R25	375	275	54	40				
	17.5R25	375	275	54	40				
914	17.5R25	375	275	54	40				
920 Standard 920 High Lift	17.5R25	500	350	72	50				
	20.5R25	375	225	54	32				





Available as OE Fitment

Replacement market only - please ask for availability

1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.

Bias Tyres for CATERPILLAR Compact Wheel Loaders



Models	Size	Ply Rating	Inflation Recommendation ¹				SGL-2A	HRL-3A
			kPa		Psi		100 (L2)	100 (L3)
			Front	Rear	Front	Rear		
910	15.5-25	12PR	375	275	54	40		
	17.5-25	12PR & 16PR	375	275	54	40		
914	17.5-25	12PR & 16PR	375	275	54	40		
918	17.5-25	12PR & 16PR	375	275	54	40		
	20.5-25	12PR	200	200	30	30		
920 Standard 920 High Lift	17.5-25	16PR	475	325	68	48		
	20.5-25	16PR	300	200	44	30		



Available as OE Fitment

1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.

Radial Tyres for CATERPILLAR Small Wheel Loaders



Models	Size	Inflation Recommendation ¹				GP-3E	TL-3A+	GP-4D	RL-5K	RT-5D
		kPa		Psi		100 (L3)	125 (L3+)	150 (L4)	250 (L5)	250 (L5)
		Front	Rear	Front	Rear					
926M	17.5R25	500	350	72	50					
	20.5R25	350	250	50	36					
930M	17.5R25	500	325	72	48					
	20.5R25	350	250	50	36					
938M	20.5R25	450	300	66	44					
	650/65R25	300	200	44	30		GP-3D			



Available as OE Fitment

Replacement market only - please ask for availability

1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.

Bias Tyres for CATERPILLAR Small Wheel Loaders



Models	Size	Inflation Recommendation ¹				SG LUG	HRL-3A	HRL-5C
		kPa		Psi		100 (L2)	100 (L3)	250 (L5)
		Front	Rear	Front	Rear			
926M	20.5-25 16PR	300	200	44	30			
930M	17.5-25 16PR	450	300	66	44			
	20.5-25	275	200	40	30			
938M	20.5-25	350	250	50	36			



Available as OE Fitment

Replacement market only - please ask for availability

1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.

Radial Tyres for CATERPILLAR Midsize Wheel Loaders



Models	Size	Inflation Recommendation ¹				GP-3E	TL-3A+	GP-4D	RL-4K	RL-5K	RT-5D
		kPa		Psi		100 (L3)	125 (L3+)	150(L4)	150 (L4)	250 (L5)	250 (L5)
		Front	Rear	Front	Rear						
950 950M	23.5R25	450	325	65	45						
	750/65R25	300	200	45	30						
962 962M	23.5R25	450	325	65	45						
	750/65R25	325	225	45	35						
966 966 XE	26.5R25	475	350	70	50						
	775/65R29	375	250	55	35						
972 972 XE	26.5R25	475	350	70	50						
	775/65R29	400	250	60	35						
980 980 XE	29.5R25	500	350	75	50						
	875/65R29	450	300	65	45						
982 982 XE	875/65R29	475	300	70	45						
	29.5R29	500	300	75	45						



Available as OE Fitment

Replacement market only - please ask for availability


1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.



Bias Tyres for CATERPILLAR Midsize Wheel Loaders




















Models	Size	Inflation Recommendation ¹				HRL EL-3A	HRL DL-5C
		kPa		Psi		115 (L3)	250 (L5)
		Front	Rear	Front	Rear		
950 / 950M	23.5-25	375	250	55	35		
962 / 962M	23.5-25	375	250	55	35		


 Replacement market only - please ask for availability


1) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).
For other applications please contact your Goodyear Representative.

Tyres for CATERPILLAR Large Wheel Loaders



Models	Size	Inflation Recommendation ¹				RL-4K	RL-5K	RT-4D	RT-5D	NRL DL-5A
		kPa		Psi		150 (L4)	250 (L5)	150 (L4)	250 (L5)	250 (L5)
		Front	Rear	Front	Rear					
986K	35/65-33	600	400	88	58					
	875/65R33	600	400	88	58					
988K 988K XE	35/65-33	600	400	88	58					
	875/65R33	650	450	94	66					
990K	1150/65R39 (45/65R39)	625	425	90	62					
992 992K	1150/65R45 (45/65R45)	625	425	90	62					
	45/65-45	625	425	90	62					

 Available as OE Fitment

 Replacement market only - please ask for availability

1) Inflation Recommendation is for Load operation speeds up to 10 km/h (5 mph).
For Load & Carry Operation add 100 kPa (15 Psi) to the inflation.
For other applications please contact your Goodyear Representative.

Radial Tyres for CATERPILLAR Articulated Dump Trucks



Models	Size	Inflation Recommendation ¹				GP-3E	TL-3A+	GP-4D
		kPa		Psi		100 (L3)	125 (E3+)	150 (L4)
		Front	Rear	Front	Rear			
725	23.5R25	350	375	50	54			
730	23.5R25	400	450	58	66			
	750/65R25	350	400	50	58			
730 EJ	750/65R25	300	400	44	58			GEN II
735	750/65R25	400	425	58	62			GEN II
740 GC	29.5R25	400	425	58	62			
	875/65R29	325	350	48	50			
740 EJ	29.5R25	375	500	58	72			
	875/65R29	300	375	44	54			
745	29.5R25	475	500	68	72			
	875/65R29	350	350	50	50			

Available as OE Fitment

Replacement market only - please ask for availability

¹) Inflation Recommendation is for speeds up to 50 km/h.
For other speeds please consult your Goodyear representative.



Radial Tyres for CATERPILLAR Medium Rigid Dump Trucks



Models	Size	Inflation Recommendation ¹				RT-4A+	RL-4H	RL-4B	RH-4A+	RM-4A+	RM-4B+
		kPa		Psi							
		Front	Rear	Front	Rear						
770G	18.00R33	850	800	124	116						
772G	21.00R33	750	750	108	108						
773G	24.00R35	700	700	102	102						
775G	24.00R35	750	750	108	108						
777	27.00R49	750	750	108	108						



Available as OE Fitment

Replacement market only - please ask for availability

¹) Inflation Recommendation is for speeds up to 50 km/h.
For other speeds please consult your Goodyear representative

Radial Tyres for CATERPILLAR Large Rigid Dump Trucks



Models	Size	RL-3+	RL-4H	RH-4A+	RL-4M+	RM-3A	RM-4A+	RM-4B+
		125 (E3)	150 (E4)	170 (E4+)	170 (E4+)	100 (E3)	170 (E4+)	170 (E4+)
785D	33.00R51							
785	33.00R51							
	36.00R51							
789	37.00R57							
	40.00R57							
793	46/90R57							
794AC	53/80R63							
795F AC	59/80R63							
796AC	59/80R63							
797F	59/80R63							
798 AC	59/80R63							



Replacement market only - please ask for availability

No Inflation Recommendation is given.
Please consult your Goodyear representative for guidance.

WARRANTY PRE-CERTIFICATION
Your application must be pre-certified by a Goodyear Representative.

GOODYEAR® OFF-THE-ROAD



GOODYEAR
OFF-THE-ROAD