

Pressure recommendations for DOOSAN

Tyres for DOOSAN
Articulated Dump Trucks



	TL-3A+ 125 (E3+)	GP-4D 150 (E4)
Abrasion and Cut Resistance	6	7
Heat Resistance	9	8
Traction	10	8
Stability	8	8
Self Cleaning	9	7
Longevity	7	8
Comfort	9	8

TYRE RATING

Abrasion and Cut Resistance

Heat Resistance

Traction

Stability

Self Cleaning

Longevity

Comfort

INFLATION RECOMMENDATION (Bar)

MODELS	DIMENSION	FRONT	REAR
DA30	750/65 R25	3.25	3.50
	23.5 R25	4.00	4.50
DA40	29.5 R25	3.75	4.75
	875/65 R29	2.75	3.25



Goodyear pressure recommendations.



DOOSAN



GOODYEAR

MADE TO FEEL GOOD.

ATTENTION

- Tyre pressure is the most important factor for tyre performance and good tyre maintenance.
- The recommended tyre pressures are for vehicles working in standard conditions and loading at nominal weight.
- It is recommended to contact your Goodyear OTR representative in order to adapt the pressures to your specific material and working conditions.

For any specific application, please contact your local Goodyear sales representative.

Produced by
Goodyear Dunlop Tyres Operations S.A.
285/0715/LUX-ENG

otr.goodyear.eu

Consult your Goodyear representative for additional information.







GOODYEAR

MADE TO FEEL GOOD.

Pressure recommendations for DOOSAN

Tyres for DOOSAN
Wheel Loaders



	RT-3B 115 (L3)	TL-3A+ 125 (L3+)	GP-4D 150 (L4)	RL-4K 150 (L4)	RL-5K 250 (L5)	RT-5D 250 (L5)
						
	Mixed Service, Comfort, Load & Carry, Sand & Gravel	Mixed Traction, Comfort, Landfill & Clay, Sidewall Protection	Load & Carry, Transport, Comfort, Stability, 65 Series	Abrasion, Recycling, Protection, Increased Tread Life	Abrasion, Recycling, Protection, Increased Tread Life	Exceptional Traction, Increased Sidewall Protection
Abrasion and Cut Resistance	7	6	7	8	9	9
Heat Resistance	8	9	8	7	5	7
Traction	8	10	8	4	5	9
Stability	8	8	8	9	9	9
Self Cleaning	7	9	7	5	5	8
Longevity	6	7	8	8	10	9
Comfort	8	9	8	7	8	8

**INFLATION
RECOMMENDATION
(Bar)**

MODELS	DIMENSION					FRONT	REAR
DL200-5	17.5 R25					5.00	3.50
	20.5 R25					3.50	2.00
DL220-5	20.5 R25					4.00	2.50
DL250-5	20.5 R25					4.25	2.75
DL300-5	23.5 R25					4.50	3.00
DL350-5	23.5 R25					4.75	3.25
DL420-5	26.5 R25					4.50	3.00
DL450-5	26.5 R25					5.00	3.50
DL550-5	29.5 R25					5.25	3.75