

---

# GOODYEAR® OFF-THE-ROAD

PRESSURE RECOMMENDATIONS FOR VOLVO.

GET THE MOST OUT OF YOUR GOODYEAR OTR TYRES

Maximise your Volvo and Goodyear OTR tyres potential by using the correct pressure.



## Radial Tyres for VOLVO Compact Wheel Loaders



### POWERLOAD

100 (L2)



Models	Size	Inflation Recommendation <sup>1</sup>				
		kPa		Psi		
		Front	Rear	Front	Rear	
L 20 Electric	335/80R18 TL EM 145A2/134B	325	250	47	36	
	365/70R18 TL EM 146A2/135B	325	250	47	36	
	405/70R18 TL EM 153A2/141B	250	200	36	29	
L 20HS	335/80R18 TL EM 145A2/134B	325	275	47	40	
	365/70R18 TL EM 146A2/135B	325	275	47	40	
	405/70R18 TL EM 153A2/141B	250	200	36	29	
L 25 Electric	335/80R18 TL EM 145A2/134B	375	275	54	40	
	365/70R18 TL EM 146A2/135B	375	275	54	40	
	405/70R18 TL EM 153A2/141B	300	200	44	29	
L 25HS	335/80R18 TL EM 145A2/134B	375	250	54	36	
	365/70R18 TL EM 146A2/135B	350	300	51	44	
	405/70R18 TL EM 153A2/141B	275	200	40	29	
L 30G L 30GS	405/70R18 TL EM 153A2/141B	325	300	47	44	
	335/80R20 TL EM 147A2/136B	375	300	54	44	only on L30G
	365/80R20 TL EM 153A2/141B	325	300	47	44	
	405/70R20 TL EM 155A2/143B	300	250	44	36	
L 35G L 35GS L 35GT	405/70R18 TL EM 153A2/141B	350	275	51	40	
	335/80R20 TL EM 147A2/136B	400	425	58	62	only on L35G
	365/80R20 TL EM 153A2/141B	350	275	51	40	
	405/70R20 TL EM 155A2/143B	325	300	47	44	

## Radial Tyres for VOLVO Compact Wheel Loaders



Models	Size	Inflation Recommendation <sup>1</sup>			
		kPa		Psi	
		Front	Rear	Front	Rear
L 45H	17.5R25	475	400	69	58
L 45HS	17.5R25	400	400	58	58
L 50H	17.5R25	425	325	62	47
L 50HS	17.5R25	425	400	62	58

GP-3E	TL-3A+	RL-5K
100 (L3)	125 (L3+)	250 (L5)
		

Available as OE Fitment

<sup>1</sup>) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).  
For other applications please contact your Goodyear Representative.

## Bias Tyres for VOLVO Wheel Loaders



Models	Size	Inflation Recommendation <sup>1</sup>			
		kPa		Psi	
		Front	Rear	Front	Rear
L 60H	17.5-25	475	325	69	47
	20.5-25	300	200	44	29
L 70H	20.5-25	375	225	54	33
L 90H	20.5-25	350	200	51	29
L 110H	23.5-25	375	225	54	33
L 120H	23.5-25	425	275	62	40
L 150H	26.5-25	425	275	62	40
L 180H	26.5-25	500	350	73	51
L 220H	29.5-25	450	300	65	44
L 350F L 350H	35/65-33	700	600	120	87

HRL D/L-3A	SGL D/L-2A	HRL D/L-5A	NRL D/L-5A	SMO D/L-5A
100 (L3)	100 (L2)	250 (L5)	250 (L5)	250 (L5S)
				
16PR	16PR			20PR
HRL D/L-3C 16PR	16PR	16PR		
HRL D/L-3C 16PR	SGL EL-2A 16PR	16PR		
HRL E/L-3A 16PR (only loading)	SGL EL-2A 16PR	HRL D/L-5A 16PR (only loading)		
20PR & 24PR (16PR only for loading)		16PR (only for loading)		
24PR (16PR & 20PR only for loading)				
				SMO D/L-5C 32PR
				SMO D/L-5C 32PR
28PR (only for loading)				
			42PR	

Available as OE Fitment

Replacement market only - please ask for availability

Proposal for Approval

<sup>1</sup>) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph).  
For other applications please contact your Goodyear Representative.

## Radial Tyres for VOLVO Wheel Loaders



Models	Size	Inflation Recommendation <sup>1</sup>				GP-3E	GP-3D	TL-3A+	GP-4D
		kPa		Psi		100 (L3)	115 (L3)	125 (L3+)	150 (L4)
		Front	Rear	Front	Rear				
L 60H	17.5R25	500	350	73	51				
	20.5R25	375	225	54	33				
	600/65R25	350	200	51	28				
L 70H	20.5R25	450	300	65	44				
	600/65R25	400	250	58	36				
L 90H	20.5R25	500	350	73	51				
	650/65R25	450	300	65	44				
L 110H	23.5R25	450	300	65	44				
	750/65R25	325	200	47	29				
L 120H	23.5R25	475	325	69	47				
	750/65R25	350	225	51	33				
L 150H	26.5R25	475	325	69	47				
	775/65R29	375	225	54	33				
L 180H	26.5R25	550	400	80	58			5.00/3.50 (only for loading)	5.00/3.50 (only for loading)
	775/65R29	425	275	62	40				
L 200H - HL	775/65R29	750	600	109	87				
	875/65R29	750	600	109	87				
L 220H	29.5R25	525	375	76	54				
	875/65R29	400	250	58	36				
L 260H	29.5R25	625	475	91	69				
	875/65R29	475	325	69	47				
L 350H	875/65R33	800	650	116	94				





Available as OE Fitment

Replacement market only - please ask for availability

<sup>1</sup>) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph) unless otherwise indicated.  
For other applications please contact your Goodyear Representative.

## Radial Tyres for VOLVO Wheel Loaders



Models	Size	Inflation Recommendation <sup>1</sup>				RL-4K	RL-5K	RT-4D	RT-5D
		kPa		Psi		150 (L4)	250 (L5)	150 (L4)	250 (L5)
		Front	Rear	Front	Rear				
L 60H	17.5R25	500	350	73	51				
	20.5R25	375	225	54	33				
	600/65R25	350	200	51	28				
L 70H	20.5R25	450	300	65	44				
	600/65R25	400	250	58	36				
L 90H	20.5R25	500	350	73	51				
	650/65R25	450	300	65	44				
L 110H	23.5R25	450	300	65	44				
	750/65R25	325	200	47	29				
L 120H	23.5R25	475	325	69	47				
	750/65R25	350	225	51	33				
L 150H	26.5R25	475	325	69	47		***		
	775/65R29	375	225	54	33				
L 180H	26.5R25	550	400	80	58		***		
	775/65R29	425	275	62	40				
L 200H - HL	775/65R29	750	600	109	87				
	875/65R29	750	600	109	87				
L 220H	29.5R25	525	375	76	54				
	875/65R29	400	250	58	36				
L 260H	29.5R25	625	475	91	69				
	875/65R29	475	325	69	47				
L 350H	875/65R33	800	650	116	94	***	***	***	***

Available as OE Fitment

Replacement market only - please ask for availability

<sup>1</sup>) Inflation Recommendation is for Load & Carry operation speeds up to 25 km/h (15 mph) unless otherwise indicated.  
For other applications please contact your Goodyear Representative.

## Radial Tyres for VOLVO Articulated Dump Trucks






Models	Size	Inflation Recommendation <sup>1</sup>				GP-3E	TL-3A	TL-3A+	TL-4A	GP-4D
		kPa		Psi		100 (E3)	115 (E3)	125 (E3+)	150 (E4)	150 (L4)
		Front	Rear	Front	Rear					
A 25 E 4x4	23.5R25 (front)	425		60						
	29.5R25 (rear)		500		75					
A 25 G	23.5R25	375	400	55	60					
	750/65R25	300	325	45	45				GEN II Available soon	
A 30 G	23.5R25	400	475	60	70					
	750/65R25	325	400	45	60					
A 35 G A 35 G FS	26.5R25	375	475	55	70					
	775/65R29	325	450	45	65					
A 40 G A 40 G FS	29.5R25	300	425	45	60					
	875/65R29	300	350	45	50					
A 45 G A 45 G FS	29.5R25	300	425	45	60					
	875/65R29	300	400	45	60					
A 60 H	33.25R29	375	500	55	75					

	Available as OE Fitment
	Replacement market only - please ask for availability
	Proposal for Approval

1) Inflation Recommendation is for speeds up to 50 km/h (30mph).  
For other speeds please consult your Goodyear Representative.

## Radial Tyres for VOLVO Rigid Dump Trucks



Models	Size	Inflation Recommendation <sup>1</sup>				RT-4A+	RM-4A+	RM-4B+
		kPa		Psi				
		Front	Rear	Front	Rear			
R60 D R60 E	24.00R35	700	700	102	102	150 (E4) / 170 (E4+)	170 (E4+)	170 (E4+)
R70 D	24.00R35	750	750	109	109			
R100 E	27.00R49	750	750	109	109			



Available as OE Fitment

Replacement market only - please ask for availability

<sup>1</sup>) Inflation Recommendation is for speeds up to 50km/h (30mph).  
For other speeds please consult your Goodyear Representative.



GOODYEAR® OFF-THE-ROAD



**GOODYEAR**  
OFF-THE-ROAD