



GOODYEAR® RH-4A+

GOODYEAR'S BEST HAULAGE TIRE FOR LONG HOURS
TO REMOVAL IN HARD ROCK UNDERFOOT CONDITIONS

■ **MADE TO WORK OVERTIME**

Extra-deep E-4+ tread depth with high net-to-gross pattern and optimized footprint pressure promotes long hours to removal

■ **KEEPS ITS COOL**

Centerline blading, shoulder lug pockets and shoulder lug side notches help cool the tire to enhance casing durability and maximize TKPH

■ **DEFENSIVE SPECIALIST**

Durawall Technology™* improves lateral stiffness, cut protection and casing durability



■ **BROAD SHOULDERED**

Wide-molded rim width^Δ promotes enhanced casing durability

■ **FIRMLY PLANTED**

Wider bead^Δ promotes enhanced lateral stability



GOODYEAR
OFF-THE-ROAD



GOODYEAR® RH-4A+



UNDERFOOT CONDITIONS

ROCK



AGGREGATES



ENGINEERING DATA

DIMENSION	DESIGN RIM/WIDTH (in)	TREAD DEPTH (mm / 32nds in)	INFLATED DIMENSIONS†		LOADED TIRE†	
			OVERALL WIDTH (mm / in)	OVERALL DIAMETER (mm / in)	LOAD SECTION & GROWTH (mm / in)	STATIC LOADED RADIUS (mm / in)
27.00R49	19.5 / 4	83.0 / 105	758 / 29.8	2,697 / 106.2	861 / 33.9	1,237 / 48.7
40.00R57	29.0 / 6	98.0 / 124	1,173 / 46.2	3,576 / 140.8	1,306 / 51.4	1,600 / 63.0
46/90R57	29.0 / 6	98.0 / 124	1,164 / 45.8	3,571 / 140.6	1,321 / 52.0	1,600 / 63.0
59/80R63	44.0 / 5	115.6 / 145	1,496 / 58.9	4,023 / 158.4	1,730 / 68.1	1,775 / 69.9

LOADS & INFLATION for off-the-road haulage service at 50 km/h (30 mph) maximum speed

DIMENSION	STAR MARKING	LOAD SPEED INDEX	LOADS PER TIRE IN KILOS / LBS AND INFLATION BAR / KPA / PSI‡						
			5.50 / 550 / 80	5.75 / 575 / 83	6.00 / 600 / 87	6.25 / 625 / 91	6.5 / 650 / 94	6.75 / 675 / 98	7.00 / 700 / 102
27.00R49	**	223B	22,400 / 49,400	23,000 / 50,700	23,600 / 52,000	25,000 / 55,100	25,750 / 56,800	26,500 / 58,400	27,250 / 60,000
40.00R57	**	250B	50,000 / 110,000	51,500 / 113,500	53,000 / 117,000	54,500 / 120,000	56,000 / 123,500	58,000 / 128,000	60,000 / 132,500
46/90R57	**	252B	53,000 / 117,000	54,500 / 120,000	56,000 / 123,500	58,000 / 128,000	60,000 / 132,500	61,500 / 135,500	63,000 / 139,000
59/80R63	**	268B	82,500 / 182,000	85,000 / 187,500	90,000 / 198,500	92,500 / 204,000	95,000 / 209,500	97,500 / 215,000	100,000 / 220,500

To learn more about the Goodyear RH-4A+, contact your local authorized Goodyear Dealer or visit goodyearotr.com

TOTAL MOBILITY



Trusted Products
Specialized OTR innovations
to help lower operating costs.



Reliable Services
Expert worldwide support to
help you optimize operations.



Tire Management Solutions
Powerful management tools to help you
improve productivity.

goodyearotr.com

†Engineering data is estimated. | ‡Tire loads and inflation conform to the 2021 standards set forth by The Tire & Rim Association and The European Tyre and Rim Technical Organisation.